

## (12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
4 January 2001 (04.01.2001)


PCT

(10) International Publication Number  
**WO 01/00918 A2**

- (51) International Patent Classification<sup>7</sup>: **D05B**
- (21) International Application Number: PCT/US00/17933
- (22) International Filing Date: 29 June 2000 (29.06.2000)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:  
60/141,434 29 June 1999 (29.06.1999) US
- (71) Applicant and  
(72) Inventor: STEFANEK, Ronald, C. [US/US]; 9537 Silica Sand Road, Garrettsville, OH 44231 (US).
- (74) Agent: FAGAN, Christopher, B.; Fay, Sharpe, Fagan, Minnich & McKee, LLP, Suite 700, 1100 Superior Avenue, Cleveland, OH 44114-2518 (US).
- (81) Designated States (*national*): AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).
- Published:  
— Without international search report and to be republished upon receipt of that report.

[Continued on next page]

(54) Title: HEMMING APPARATUS AND METHOD



(57) Abstract: In accordance with the present invention, an improved apparatus and method for prehemming and hemming is provided. More particularly, the improved apparatus and method is for folding an edge portion of a curved arcuate panel to create a hem in a single cycle of operation with a single hemming swing steel pressed only in the vertical direction. The apparatus and method use an anvil for supporting an associated assembly of the outer skin and the inner panel, an upper body, and a steel mounted to the upper

[Continued on next page]

WO 01/00918 A2